















SLOW MOTON We slow down the movement, not your work.



In normal reels, the cable returns to its seating quickly and uncontrollably, requiring the operator to accompany it, which means time wasted. To help resolve this issue, in 2010 Mavel - a manufacturer of high-quality reels, designed and patented the very first and one-of-a-kind external device that can be easily installed and removed.

A simple yet ingenious idea. Slow Motion is in fact an optional, high-performance device that controls and slows down rewinding, in a uniform manner, thereby eliminating jerking and whiplash. The result? Improved safety, a tidier working environment, and less time wasted.

Mavel Slow Motion: easy to install, practical to use, simple to replace.





Code	Energy	Lights	Air
Roll Classic PLUS	707010	707010	707010
Roll Master PLUS	707020	707020	707020
Roll Dynamic 230V - Air	707015	707015	707005
Roll Dynamic 400V	707005	-	-
Roll Compact 12/24/230V - Air	707040	707040	707030
Roll Compact 400V	707030	-	-
Roll Major PLUS	707000	707000	707000







A step into the future, here and now. Electric cars are a rapidly-developing reality and an electric cable without a reel is like a smartphone with no connection!

Which is why Mavel came up with and designed a convenient automatic reel, the EV charging reel, the perfect accessory for your wall box.

Thanks to our EV charging reel, the electric cable used to charge your car will always be unwound to the perfect length, thereby avoiding the annoyance of it resting on the ground, exposed to dirt and pollutants, in addition to risking its rapid deterioration.

Perfect for private use, corporate car parks, hotel garages and any location where having a charging source on hand is a necessity.

The EV charging reel comes with a 5 m cable with type 2 connectors (on the wall box side), and your choice of type 1 or type 2 connectors on the car side. In addition, thanks to the exclusive Slow Motion safety system, which slowly retracts the cable, the Mavel cable reel for electric cars satisfies even the most demanding convenience and security.

Roll Compact EV Charging Reel



808220

0	4 + 1 m
6	3,6 kW 16 A - 230 V
G a	4,6 kW 20 A - 230 V
CABLE	3G2,5+1x0,5 Type 2



MADE IN ITALY

Designed and Manufactured



Roll Classic Plus LAN Cable



Roll Master Plus Warning Tape Reel



Roll Compact Warning Tape Reel



Roll Compact Car Charging Cables







	8		1		
			Mayor	Ē	
	1				
,	M	6	8		

	811600
R	4 x (2 x 0,15) mm ²
0	15 m
CABLE	CAT 5e
V max	48 V
A max	2 A

	811700	811720
0	16 m	16 m

	808400	808420	
0	20 m	20 m	

	809110
À	2x
Sezione	16 mm ²
0	6 m
A max	30 A

Lighty LED



Sirio_15		
	C	
<u>}</u>	7	
	П	
_	ш	
	Ш	



lights	
Rollamp Classic Plus	slow motion 707210

	830118
(A)	10 m
\bigcirc	2x1 mm ²
CABLE	H05W-F
100000	18 LED - 900 LUMEN

(0) CABLE

1000000


830122

18 LED - 900 LUMEN

Light source	
15 SI	MD LED high brightness
Luminous flux	
	360 lm Standard mode
	500 lm boost mode
Battery	3,7V 3000mAh LiPo
Battery charge	r USB adapter
	mini USB 230V
Charging time	5 h
Duration of ligh	nt
	5 h Standard mode

3 1/2" h Boost mode

830300



230>24V	811340
(A)	15 m
\bigcirc	2x1 mm ²
CABLE	H05RN-F
	MAX
96	600 W
	E27



12V>12V	
24V>24V	811480
(A)	15 m
\bigcirc	2x1 mm ²
CABLE	H05RN-F
6/	10 W
96	900 Lumen
F 1000000	18 LED
• • • • • • • • • • • • • • • • • • • •	10 LLD
	10 LLD
230>24V	811460
	811460
	811460 15 m
230>24V O	811460 15 m 2x1 mm²
230>24V O	811460 15 m 2x1 mm ² H05RN-F



A BURST OF ENERGY FOR YOUR BUSINESS

Optimize productivity and safety with the retractable electric cable reels from **Mayel**:

- · Organisation: a place for every cable and every cable in its place!
- Time-saving: no more knots, tangles, or cables spread over the floor.
- Integrity and duration: cables perfectly wound and protected, thus reducing damage and wear to a minimum.
- Protection and safety: the operator can move more freely and concentrate on the task at hand without having to risk tripping and slipping...

General characteristics:

- · Shockproof plastic structure.
- Available with various types of cable: in PVC (H05VV-F) or high-quality rubber, either single-phase or three-phase. Lengths from 6 to 35 metres.
- Circuit protection against thermal or amperometric overloads.
- Device to block cable at the desired length (it can be disabled if continuous drive is needed).

Optional: SLOWMOTION system, can be applied to most of the **ENERGY** series.

Roll Minor



230V	800150
<u></u>	5+1 m
\bigcirc	3G1,5 mm ²
CABLE	H05W-F
6/	800 W
96 -	2000 W
	SCHUKO

Roll Classic Plus





230V	811200
<u></u>	10 m
	3G1,5 mm ²
CABLE	H05VV-F
	800 W
9/6	2000 W
6	SCHUKO

Roll Master Plus





230V	811030	811055
(O	15 m	10 m
<u></u>	3G1,5 mm ²	3G2,5 mm ²
CABLE	H05VV-F	H07RN-F
6 /	800 W	1600 W
% 6 -	2000 W	3000 W
6	SCHUKO	SCHUKO

Roll Dynamic



Roll Compact







Roll Mega



230V	826040
(A)	18 m
	3G1,5 mm ²
CABLE	H05VV-F
	800 W
96	2000 W
P	SCHUKO



230V	808742	808757
(a)	18 m	15 m
	3G1,5 mm ²	3G2,5 mm ²
CABLE	H05VV-F	H07RN-F
6/_	800 W	1600 W
% 6 -	2000 W	3000 W
P	SCHUKO	SCHUKO



230V	820705	820722
(0)	25 m	20 m
\bigcirc	3G1,5 mm ²	3G2,5 mm ²
CABLE	H05VV-F	H07RN-F
6 /	800 W	1600 W
% 6 -	2000 W	3000 W
F	SCHUKO	SCHUKO

400V	820896
<u></u>	15 m
	5G2,5 mm ²
CABLE	H07RN-F
	2800 W
%6	5000 W
6	EUROPE



230V	880450
<u></u>	35 m
	3G1,5 mm ²
CABLE	H05W-F
	800 W
96 -	2000 W
P	SCHUKO
400V	880850

400V	880850
<u></u>	25 m
<u></u>	5G2,5 mm ²
CABLE	H07RN-F
	2800 W
9/6	5000 W
6	EUROPE



A BREATH OF FRESH AIR!

The **Mavel** retractable hose reels are an essential tool for your business, greatly appreciated by operators. The device offers many advantages: hoses always of the right length, handily unwound and rewound, with no knots, undamaged and protected.

Order and cleanliness in the workplace, practicality, time-saving, and increased productivity round out the list of pros that make this accessory an absolute must.

General characteristics:

- · Shockproof plastic structure with metal bracket.
- Available with different types of hoses: in PU or high-quality PU/PVC blend for pressures up to 20 bar. Lengths from 6 to 20 metres.
- Device to block cable at the desired length (it can be disabled if continuous drive is needed).

Optional: SLOWMOTION system, can be applied to most of the **AIR** series.

Roll Minor



	810010
0	5+1 m
Ø	6x8 mm 1/4"
(b)=bar	10 bar
(a) AIR	Max 10 bar
WATER	NO

Roll Master Plus



804200

8x12 mm

Max 10 bar

Max 40° C

9 m

1/4"

10 bar

Roll Dynamic Air





	826300	826400
0	12 m	8 m
Ø	8x12 mm 1/4"	10x15 mm 3/8"
(b)=bar	15 bar	15 bar
(a) AIR	Max 15 bar	Max 15 bar
WATER	Max 40° C	Max 40° C

Roll Compact



Roll Major Plus





WATER




	880100	880200
0	20 m	15+1 m
Ø	10x15 mm 3/8"	12x17,5 mm 1/2"
(b)=bar	15 bar	15 bar
(a) AIR	Max 15 bar	Max 15 bar
WATER	Max 40° C	Max 40° C

Roll Profi Open



	860650	860660
0	16+2 m	13+2 m
Ø	10x15 mm 3/8"	13x18 mm 1/2"
(b)=bar	20 bar	20 bar
(a) AIR	Max 20 bar	Max 20 bar
WATER	Max 40° C	Max 40° C







"FLUIDS"... AND EVERYTHING FLOWS SMOOTHLY!

A family of retractable reels for fluids capable of facilitating and optimizing a day's work. The standard version comes with a swivel and fixed steel bracket (The standard Roll PROFI comes only with the swiveling bracket, but can be supplied with a fixed bracket upon request), suitable to be installed on the wall, ceiling or floor.

The reel structure is made in solid, shockproof plastic. Available without hoses or with different lengths and sections of hose (from 15m 1/4" to 20m ½").

Suitable for conveying:

- · Oil: max 60bar 40°C
- · Water: max 200 bar 150°C

Roll Profi



OUT B	3/8"F
OIL	Max 60 bar / 40° C

860220

	860320
O	15 m - 3/8"
IN IN	1/2"M
OUT	3/8"F
WATER	Max 200 bar / 150° C

Roll Profi Open



(O)	15 m - 3/8"
<u>H</u> E IN	1/2"M
оит -	3/8"F
OIL	Max 60 bar / 40° C
	260620

860520

	000020
0	15 m - 3/8"
IIIE IN	1/2"M
OUT -	3/8"F
WATER	Max 200 bar / 150° C

Roll Big Profi



	860930
0	19+1 m - 3/8"
III IN	1/2"M
OUT -	3/8"F
OIL	Max 60 bar / 40° C

	860935
0	20 m - 3/8"
III IN	1/2"M
оит 🔚	3/8"F
WATER	Max 200 bar / 150° C

FOR TRUE RELAXATION WHILE GARDENING...

The **GARDEN** series is a must. Constructed according to the strictest quality standards, made completely in shockproof plastic, practical and functional, this device ensures an orderly winding of the hose, making it easier and safer for enthusiasts and professionals alike.

Available hose lengths:

20m or 30 m, ½", or 20m, 5%".

ROLL MAXI EVO with optional SLOW MOTION system: gradual winding of the hose in complete safety without tearing or whiplash.

Roll Maxi Evo



	844150
0	20 m
Ø	11x15 mm 1/2"
(b) = bar	6 bar
MAX	Max 40° C

Roll Maxi



	840310	840410
0	30 m	20 m
\varnothing	11x15 mm 1/2"	15x19 mm 5/8"
>=bar	6 bar	6 bar
MAX	Max 40° C	Max 40° C



EV reel energy slow motion lights special app fluids garden air

Mavel srl

36035 Marano Vic.no · VI · Italy Via Progresso, 76 T +39 0445.622.997 F +39 0445.560.454 mavel@mavel.it